

CARBIDE, 3 FLUTE 40° HELIX CORNER RADIUS LONG LENGTH

-  **VOLLHARTMETALL, 3 SCHNEIDN 40° RECHTSSPIRALE ECKENRADIUS LANG**
-  **Fraise carbure, 3 dents, torique, hélice 40°, longue**
-  **3 TAGLIENTI, ELICA 40°, TORICA, SERIE LUNGA**

- Higher hardness of film and excellent wear-resistance increase the tool life surprisingly.

► Ultra fine film of YG-1's diamond coated carbide end mills ensure the smooth and excellent surface on work materials.

► High performance on graphite, wrought aluminum, bakelite, plastics, wood, brass etc. YG-1's diamond coated carbide end mills have good result for the machining of non-ferrous metals and non-metallic materials.
- Höhere Härte der Beschichtung und ausgezeichnete Verschleißfestigkeit verlängern die Standzeit beachtlich.

► Ultrafeiner Film auf YG-1 Diamant - beschichteten Hartmetall Schafffräser gewährleisten eine glatte und ausgezeichnete Oberflächengüte.

► Hohe Leistungsfähigkeit bei Graphit, Aluminium ohne Silicon, Bakelit, Plastik, Holz, Messing, etc. YG-1 Diamant - beschichtete Hartmetall Schafffräser zeigen gute Ergebnisse beim Bearbeiten von NE - Metallen und Nichtmetall - Werkstoffen.



 Recommended ToolHolder	Plain Shank		Page
		HYDRAULIC CHUCK	D15 - 46
		SHRINK FIT HOLDER	D47 - 72
		POWER MILLING CHUCK	D161 - 176
		ER COLLET CHUCK	D73 - 116
		SK SLIM CHUCK	D183 - 201

Unit : mm

EDP No.	Corner Radius	Mill Diameter	Shank Diameter	Length of Cut	Overall Length
	R	D1	D2	L1	L2
EIA14020	R0.15	2.0	3	9	60
EIA14030	R0.15	3.0	3	30	60
EIA14040	R0.2	4.0	4	30	60
EIA14050	R0.3	5.0	5	35	70
EIA14060	R0.3	6.0	6	40	100
EIA14080	R0.5	8.0	8	40	100
EIA14100	R0.5	10.0	10	40	100
EIA14120	R0.5	12.0	12	45	100

Mill Dia. Tolerance (mm)	Shank Dia. Tolerance
0 ~ - 0.03	h5



◎ : Excellent ○ : Good

ISO	P										M				K					
Material Description	Non-alloy steel					Low alloy steel				High alloyed steel, and tool steel		Stainless steel			Grey cast iron		Nodular cast iron		Malleable cast iron	
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
HRc		13	25	28	32	10	29	32	38	15	35	15	23	10	10	26	3	25		21
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230
Recommend																				
ISO	N										S						H			
Material Description	Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials		Heat Resistant Super Alloys					Titanium Alloys		Hardened steel	Chilled Cast Iron	Hardened Cast Iron
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
HRc											15	30	25	38	34			55	60	42
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400 Rm	1050 Rm	550	630	400
Recommend	○	○	○	○	○				◎											